



## Safety Data Sheet

prepared to UN GHS Revision 3

### 1. Identification of the Substance/Mixture and the Company/Undertaking

1.1	Product Identifier	425-0002	Revision Date:	13/05/2015
	Product Name:	Carboclad 938 HB	Supersedes Date:	New SDS
1.2	Relevant identified uses of the substance or mixture and uses advised against	Monocomponent industrial coating - Industrial use.		
1.3	Details of the supplier of the safety data sheet			
	Importer:	None		
	Manufacturer:	StonCor Africa (Pty.) Ltd. 8 Cresset Road Midrand Industrial Park, Chloorkop P.O. Box 2205 2001, Johannesburg South Africa		
		Regulatory /Technical Information: +27 11 254 5500		
	Datasheet Produced by:	Maritz, Rory - ehs@stoncor.com		
1.4	Emergency telephone number:	CHEMTREC 1-800-424-9300 (Inside US) CHEMTREC +1 703 5273887 (Outside US)		

### 2 Hazard Identification

#### 2.1 Classification of the substance or mixture

Hazardous to the aquatic environment, Chronic, category 3  
Carcinogenicity, category 1A  
STOT, single exposure, category 1  
Skin Irritation, category 2

#### 2.2 Label elements

##### Symbol(s) of Product



##### Signal Word

Danger

##### Named Chemicals on Label

quartz (silicon dioxide)

##### HAZARD STATEMENTS

Hazardous to the aquatic environment, Chronic, category 3	H412	Harmful to aquatic life with long lasting effects.
Carcinogenicity, category 1A	H350-1A	May cause cancer.
STOT, single exposure, category 1	H370	Causes damage to organs.
Skin Irritation, category 2	H315	Causes skin irritation.

**PRECAUTION PHRASES**

P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P264	Wash hands thoroughly after handling.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P284	Wear respiratory protection.
P307+311	IF exposed, call a POISON CENTER or doctor/physician.
P308+313	IF exposed or concerned: Get medical advice/attention
P314	Get medical advice/attention if you feel unwell.
P332+313	If skin irritation occurs: Get medical advice/attention.

**2.3 Other hazards**

Not applicable

**Results of PBT and vPvB assessment**

The product does not meet the criteria for PBT/VPvB in accordance with Annex XIII.

**3. Composition/Information On Ingredients****3.2 Mixtures****Hazardous Ingredients**

<u>CAS-No.</u>	<u>Chemical Name</u>	<u>%</u>
1330-20-7	xylene	25-50
14808-60-7	quartz (silicon dioxide)	10-25
64742-95-6	solvent naphtha (petroleum), light arom.	2.5-10
100-41-4	ethylbenzene	2.5-10
13463-67-7	titanium dioxide	2.5-10
107-98-2	1-methoxypropan-2-ol	1.0-2.5
64-17-5	ethanol	0.1-1.0
64742-88-7	solvent naphtha (petroleum), medium aliph.	0.1-1.0
141-78-6	ethyl acetate	<0.1
1589-47-5	2-methoxypropanol	<0.1

<u>CAS-No.</u>	<u>GHS Symbols</u>	<u>GHS Hazard Statements</u>	<u>M-Factors</u>
1330-20-7	GHS02-GHS07	H226-312-315-332	0
14808-60-7	GHS08	H350-370	0
64742-95-6	GHS02-GHS08-GHS09	H226-304-411	0
100-41-4	GHS02-GHS07-GHS08	H225-304-315-319-332-373	0
13463-67-7	GHS07-GHS08	H335-373-413	0
107-98-2	GHS02-GHS07	H226-336	0
64-17-5	GHS02-GHS07	H225-319	0
64742-88-7	GHS08	H304	0
141-78-6	GHS02-GHS07	H225-319-336	0
1589-47-5	GHS02-GHS05-GHS07-GHS08	H226-315-318-335-360	0

**Additional Information:** The text for GHS Hazard Statements shown above (if any) is given in Section 16.**4. First-aid Measures****4.1 Description of First Aid Measures****GENERAL NOTES:** When symptoms persist or in all cases of doubt seek medical advice.**AFTER INHALATION:** Move to fresh air. Consult a physician after significant exposure.**AFTER SKIN CONTACT:** Use a mild soap if available. Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If skin irritation persists, call a physician.**AFTER EYE CONTACT:** Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses.**AFTER INGESTION:** Gently wipe or rinse the inside of the mouth with water. Give small amounts of water to drink. Do NOT

induce vomiting. Never give anything by mouth to an unconscious person.

#### Self protection of the first aider:

No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

#### 4.2 Most important symptoms and effects, both acute and delayed

No Information

#### 4.3 Indication of any immediate medical attention and special treatment needed

No information available on clinical testing and medical monitoring. Specific toxicological information on substances, if available, can be found in section 11.

## 5. Fire-fighting Measures

### 5.1 Extinguishing Media:

Carbon Dioxide, Dry Chemical, Foam, Water Fog

**FOR SAFETY REASONS NOT TO BE USED:** Alcohol, Alcohol based solutions, any other media not listed above.

### 5.2 Special hazards arising from the substance or mixture

No Information

### 5.3 Advice for firefighters

Flash back possible over considerable distance. In the event of fire, wear self-contained breathing apparatus. Do not use a solid water stream as it may scatter and spread fire. Hazardous decomposition products formed under fire conditions. Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

## 6. Accidental Release Measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation. Use personal protective equipment. Remove all sources of ignition.

### 6.2 Environmental precautions

Do not allow material to contaminate ground water system. Prevent product from entering drains.

### 6.3 Methods and material for containment and cleaning up

Prevent further leakage or spillage if safe to do so. Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local /national regulations (see section 13).

### 6.4 Reference to other sections

Please refer to disposal requirements or country specific disposal requirements for this material. See Section 13 for further information.

## 7. Handling and Storage

### 7.1 Precautions for safe handling

**INSTRUCTIONS FOR SAFE HANDLING:** Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Vapours may form explosive mixtures with air. Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits. Electrical equipment should be protected to the appropriate standard. Preparation may charge electrostatically: always use earthing leads when transferring from one container to another. Use only in area provided with appropriate exhaust ventilation. To avoid ignition of vapours by static electricity discharge, all metal parts of the equipment must be grounded. Wear personal protective equipment. Do not breathe vapours or spray mist. Use only explosion-proof equipment. Keep away from sources of ignition - No smoking.

**PROTECTION AND HYGIENE MEASURES:** Wash hands before breaks and at the end of workday. When using, do not eat, drink or smoke.

### 7.2 Conditions for safe storage, including any incompatibilities

**CONDITIONS TO AVOID:** Direct sources of heat

**STORAGE CONDITIONS:** Store in original container. Keep locked up or in an area accessible only to qualified or authorised persons. Store in a dry, well ventilated place away from sources of heat, ignition and direct sunlight

### 7.3 Specific end use(s)

No specific advice for end use available.

## 8. Exposure Controls/Personal Protection

### 8.1 Control parameters

#### Ingredients with Occupational Exposure Limits

(EU)

Name	%	LTEL ppm	STEL ppm	STEL mg/m <sup>3</sup>	LTEL mg/m <sup>3</sup>	OEL Note
xylene	25-50	50	100	442	221	SK
quartz (silicon dioxide)	10-25					
solvent naphtha (petroleum), light arom.	2.5-10					
ethylbenzene	2.5-10	100	200	884	442	SKIN
titanium dioxide	2.5-10					
1-methoxypropan-2-ol	1.0-2.5	100	150	568	375	SKIN
ethanol	0.1-1.0					
solvent naphtha (petroleum), medium aliph.	0.1-1.0					
ethyl acetate	<0.1					
2-methoxypropanol	<0.1					

**FURTHER INFORMATION:** Refer to the regulatory exposure limits for the workforce enforced in each country.

### 8.2 Exposure controls

#### Personal Protection

**RESPIRATORY PROTECTION:** Respirator with a vapor filter.

**EYE PROTECTION:** Tightly fitting safety goggles.

**HAND PROTECTION:** Rubber or plastic gloves. Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact). Long sleeved clothing. Remove and wash contaminated clothing before re-use.

**OTHER PROTECTIVE EQUIPMENT:** No Information

**ENGINEERING CONTROLS:** Avoid contact with skin, eyes and clothing. Ensure adequate ventilation, especially in confined areas.

## 9. Physical and Chemical Properties

### 9.1 Information on basic physical and chemical properties

Appearance:	Viscous Liquid
Physical State	Liquid
Odor	Solvent
Odor threshold	Not determined
pH	Not determined
Melting point /freezing point (°C)	Not determined
Boiling point/range (°C)	77 - 138
Flash Point, (°C)	999
Evaporation rate	Slower than ether
Flammability (solid, gas)	Not determined
Upper/lower flammability or explosive limits	0.8 - 12.3
Vapour Pressure	Not determined
Vapour density	Heavier than air
Relative density	1.22 - 1.27
Solubility in /Miscibility with water	Not determined
Partition coefficient: n-octanol/water	Not determined

<b>Auto-ignition temperature (°C)</b>	Not determined
<b>Decomposition temperature (°C)</b>	Not determined
<b>Viscosity</b>	70 - 80 kU
<b>Explosive properties</b>	Not determined
<b>Oxidising properties</b>	Not determined

**9.2 Other information**

<b>VOC Content g/l:</b>	585
<b>Calculated grams of VOC per liter of coating product as applied.</b>	
<b>Specific Gravity (g/cm<sup>3</sup>)</b>	1.255

## 10. Stability and Reactivity

**10.1 Reactivity**

No reactivity hazards known under normal storage and use conditions.

**10.2 Chemical stability**

Stable under recommended storage conditions. Risk of ignition.

**10.3 Possibility of hazardous reactions**

Hazardous polymerisation does not occur.

**10.4 Conditions to avoid**

Direct sources of heat

**10.5 Incompatible materials**

Strong oxidizing agents.

**10.6 Hazardous decomposition products**

Carbon dioxide (CO<sub>2</sub>), carbon monoxide (CO), oxides of nitrogen (NO<sub>x</sub>), dense black smoke.

## 11. Toxicological Information

**11.1 Information on toxicological effects****Acute Toxicity:**

**Oral LD50:**

**Inhalation LC50:**

**Irritation:** No information available.

**Corrosivity:** No information available.

**Sensitization:** No information available.

**Repeated dose toxicity:** No information available.

**Carcinogenicity:** No information available.

**Mutagenicity:** No information available.

**Toxicity for reproduction:** No information available.

If no information is available above under Acute Toxicity then the acute effects of this product have not been tested. Data on individual components are tabulated below.

<u>CAS-No.</u>	<u>Chemical Name</u>	<u>Oral LD50</u>	<u>Dermal LD50</u>	<u>Vapor LC50</u>
1330-20-7	xylene	4300 mg/kg, rat, oral		15000 ppm/4 hrs rat, inhalation

64742-95-6	solvent naphtha (petroleum), light arom.	4700 mg/kg, oral, rat	>2000 mg/kg	3670 ppm/8 hours, rat inhalation
100-41-4	ethylbenzene	3500 mg/kg rat oral		
13463-67-7	titanium dioxide	10000 mg/m <sup>3</sup> , oral (rat)		
107-98-2	1-methoxypropan-2-ol	5180 mg/kg, oral, rat		10000 ppm/4hrs rat inhalation
64-17-5	ethanol	7060 mg/kg, oral, rat		20000 ppm/10 hrs, rat inhalation
64742-88-7	solvent naphtha (petroleum), medium aliph.	>2000 mg/kg, oral, rat		
141-78-6	ethyl acetate	5600 mg/kg oral, rat		56000 mg/l/4h. (rat)
1589-47-5	2-methoxypropanol	5710 mg/kg, oral, rat		

**Additional Information:**

No Information

## 12 Ecological Information

**12.1 Toxicity:**

<b>EC50 48hr (Daphnia):</b>	No information
<b>IC50 72hr (Algae):</b>	No information
<b>LC50 96hr (fish):</b>	No information

**12.2 Persistence and degradability:** No information**12.3 Bioaccumulative potential:** No information**12.4 Mobility in soil:** No information**12.5 Results of PBT and vPvB assessment:** The product does not meet the criteria for PBT/vPvB in accordance with Annex XIII.**12.6 Other adverse effects:** No information

<u>CAS-No.</u>	<u>Chemical Name</u>	<u>EC50 48hr</u>	<u>IC50 72hr</u>	<u>LC50 96hr</u>
1330-20-7	xylene	No information	No information	
14808-60-7	quartz (silicon dioxide)	No information	No information	
64742-95-6	solvent naphtha (petroleum), light arom.	>1 - 10 mg/l	>1 - 10 mg/l	>10-100 mg/l
100-41-4	ethylbenzene	No information	No information	
13463-67-7	titanium dioxide	>100 mg/l (EC50, 48h, Daphnia magna OECD202)ation	No information	>1000 mg/l
107-98-2	1-methoxypropan-2-ol	No information	No information	
64-17-5	ethanol	No information	No information	
64742-88-7	solvent naphtha (petroleum), medium aliph.	No information	No information	
141-78-6	ethyl acetate	No information	No information	
1589-47-5	2-methoxypropanol	No information	No information	

## 13. Disposal Considerations

**13.1 WASTE TREATMENT METHODS:** Do not burn, or use a cutting torch on, the empty drum. If recycling is not practicable, dispose of in compliance with local regulations. Empty containers should be taken to an approved waste handling site for recycling or disposal.

## 14. Transport Information

14.1	UN number	1263
14.2	UN proper shipping name	Paint
	Technical name	
14.3	Transport hazard class(es)	3
	Subsidiary shipping hazard	
14.4	Packing group	II
14.5	Environmental hazards	
14.6	Special precautions for user	Not applicable
	EmS-No.:	
14.7	Transport in bulk according to Annex II of MARPOL 73/78 and the IBC code	Not applicable

## 15. Regulatory Information

### 15.1 Safety, health and environmental regulations/legislation for the substance or mixture:

#### National Regulations:

Denmark Product Registration Number:

Danish MAL Code:

Sweden Product Registration Number:

Norway Product Registration Number:

WGK Class:

### 15.2 Chemical Safety Assessment

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

## 16. Other Information

### Text for GHS Hazard Statements shown in Section 3 describing each ingredient:

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H350	May cause cancer.
H360	May damage fertility or the unborn child.
H370	Causes damage to organs.
H373	May cause damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.
H413	May cause long lasting harmful effects to aquatic life.

### Reasons for revision

No Information

### List of References:

This Safety Data Sheet was compiled with data and information from the following sources:

The Ariel Regulatory Database provided by the 3E Corporation in Copenhagen, Denmark

ESIS (The European Chemical Substances Information System), provided by the European Commission Joint Research Centre in Ispra, Italy  
 Annex VI of the EU Council Directive 67/548/EEC  
 Council Directive 67/548/EEC - Annex I or EU Council Directive 1999/45/EC  
 European Union (EC) Regulation No. 1272/2008 on the classification, labelling and packaging of substances and mixtures (CLP Regulation)  
 EU Council Decision 2000/532/EC and its Annex entitled "List of Wastes"

## Acronym &amp; Abbreviation Key:

CLP	Classification, Labeling & Packaging Regulation
EC	European Commission
EU	European Union
US	United States
CAS	Chemical Abstract Service
EINECS	European Inventory of Existing Chemical Substances
REACH	Registration, Evaluation, Authorization of Chemicals Regulation
GHS	Globally Harmonized System of Classification and Labeling of Chemicals
LTEL	Long term exposure limit
STEL	Short term exposure limit
OEL	Occupational exposure limit
ppm	Parts per million
mg/m <sup>3</sup>	Milligrams per cubic meter
TLV	Threshold Limit Value
ACGIH	American Conference of Governmental Industrial Hygienists
OSHA	Occupational Safety & Health Administration
PEL	Permissible Exposure Limits
VOC	Volatile organic compounds
g/l	Grams per liter
mg/kg	Milligrams per kilogram
N/A	Not applicable
LD50	Lethal dose at 50%
LC50	Lethal concentration at 50%
EC50	Half maximal effective concentration
IC50	Half maximal inhibitory concentration
PBT	Persistent bioaccumulative toxic chemical
vPvB	Very persistent and very bioaccumulative
EEC	European Economic Community
ADR	International Transport of Dangerous Goods by Road
RID	International Transport of Dangerous Goods by Rail
UN	United Nations
IMDG	International Maritime Dangerous Goods Code
IATA	International Air Transport Association
MARPOL	International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978
IBC	International Bulk Container

For further information, please contact: Technical Services Department

The information on this sheet corresponds to our present knowledge. It is not a specification and it does not guarantee specific properties. The information is intended to provide general guidance as to health and safety based upon our knowledge of the handling, storage, and use of the product. It is not applicable to unusual or non-standard uses of the product or where instructions and recommendations are not followed.