



Safety Data Sheet

prepared to UN GHS Revision 3

1. Identification of the Substance/Mixture and the Company/Undertaking

1.1	Product Identifier	504-0003	Revision Date:	06/11/2015
	Product Name:	Carbocoat GP-55 - Primer	Supersedes Date:	New SDS
1.2	Relevant identified uses of the substance or mixture and uses advised against	Monocomponent industrial coating - Industrial use.		
1.3	Details of the supplier of the safety data sheet			
	Importer:	None		
	Manufacturer:	StonCor Africa (Pty.) Ltd. 8 Cresset Road Midrand Industrial Park, Chloorkop P.O. Box 2205 2001, Johannesburg South Africa		
		Regulatory /Technical Information: +27 11 254 5500		
	Datasheet Produced by:	Maritz, Rory - ehs@ stoncor.com		
1.4	Emergency telephone number:	CHEMTREC 1-800-424-9300 (Inside US) CHEMTREC +1 703 5273887 (Outside US)		

2 Hazard Identification

2.1 Classification of the substance or mixture

Hazardous to the aquatic environment, Chronic, category 2
Flammable Liquid, category 2
Skin Irritation, category 2

2.2 Label elements

Symbol(s) of Product



Signal Word

Danger

Named Chemicals on Label

None

HAZARD STATEMENTS

H411 Toxic to aquatic life with long lasting effects.

Hazardous to the aquatic environment,
Chronic, category 2

Other EU extensions	EUH208	Contains a mixture of: butan-2-one oxime; syn-o,o'-di (butan-2-one oxime)diethoxysilane, cobalt 2-ethylhexanoate, fatty acids c18 reaction prod. with n,n-dimethyl-1,3-propanediammina & 1,3-propandiamina. May produce an allergic reaction.
Flammable Liquid, category 2	H225	Highly flammable liquid and vapour.
Skin Irritation, category 2	H315	Causes skin irritation.

PRECAUTION PHRASES

P210	Keep away from heat/sparks/open flames/hot surfaces. –No smoking.
P235	Keep cool.
P273	Avoid release to the environment
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P332+313	If skin irritation occurs: Get medical advice/attention.
P391	Collect spillage.
P403+233	Store in a well-ventilated place. Keep container tightly closed.

2.3 Other hazards

No Information

Results of PBT and vPvB assessment

The product does not meet the criteria for PBT/vPvB in accordance with Annex XIII.

3. Composition/Information On Ingredients**3.2 Mixtures****Hazardous Ingredients**

<u>CAS-No.</u>	<u>Chemical Name</u>	<u>%</u>
1330-20-7	xylene	10-25
7779-90-0	trizinc bis(orthophosphate)	2.5-10
100-41-4	ethylbenzene	2.5-10
13463-67-7	titanium dioxide	2.5-10
546-93-0	magnesium carbonate	1.0-2.5
64-17-5	ethanol	0.1-1.0
64742-88-7	solvent naphtha (petroleum), medium aliph.	0.1-1.0
96-29-7	a mixture of: butan-2-one oxime; syn-o,o'-di(butan-2-one oxime)diethoxysilane	0.1-1.0
136-52-7	cobalt 2-ethylhexanoate	0.1-1.0
117-81-7	bis(2-ethylhexyl) phthalate	<0.1
71-36-3	butan-1-ol	<0.1
141-78-6	ethyl acetate	<0.1

<u>CAS-No.</u>	<u>GHS Symbols</u>	<u>GHS Hazard Statements</u>	<u>M-Factors</u>
1330-20-7	GHS02-GHS07	H226-312-315-332	0
7779-90-0	GHS07-GHS09	H302-400-410	0
100-41-4	GHS02-GHS07-GHS08	H225-304-315-319-332-373	0
13463-67-7	GHS07-GHS08	H335-373-413	0
546-93-0	GHS07	H319	0
64-17-5	GHS02-GHS07	H225-319	0
64742-88-7	GHS08	H304	0
96-29-7	GHS05-GHS07-GHS08	H312-317-318-351	0
136-52-7	GHS07-GHS09	H317-400	1
117-81-7	GHS08	H360	0
71-36-3	GHS02-GHS05-GHS07	H226-315-318-335-336	0
141-78-6	GHS02-GHS07	H225-319-336	0

Additional Information: The text for GHS Hazard Statements shown above (if any) is given in Section 16.

4. First-aid Measures**4.1 Description of First Aid Measures**

GENERAL NOTES: When symptoms persist or in all cases of doubt seek medical advice.

AFTER INHALATION: Move to fresh air. Consult a physician after significant exposure.

AFTER SKIN CONTACT: Use a mild soap if available. Wash off immediately with soap and plenty of water while removing

all contaminated clothes and shoes. If skin irritation persists, call a physician.

AFTER EYE CONTACT: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses.

AFTER INGESTION: Gently wipe or rinse the inside of the mouth with water. Give small amounts of water to drink. Do NOT induce vomiting. Never give anything by mouth to an unconscious person.

Self protection of the first aider:

No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

4.2 Most important symptoms and effects, both acute and delayed

No Information

4.3 Indication of any immediate medical attention and special treatment needed

No information available on clinical testing and medical monitoring. Specific toxicological information on substances, if available, can be found in section 11.

5. Fire-fighting Measures

5.1 Extinguishing Media:

Carbon Dioxide, Dry Chemical, Foam

FOR SAFETY REASONS NOT TO BE USED: Alcohol, Alcohol based solutions, any other media not listed above.

5.2 Special hazards arising from the substance or mixture

No Information

5.3 Advice for firefighters

Flash back possible over considerable distance. In the event of fire, wear self-contained breathing apparatus. Do not use a solid water stream as it may scatter and spread fire. Hazardous decomposition products formed under fire conditions. Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

6. Accidental Release Measures

6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation. Use personal protective equipment. Remove all sources of ignition.

6.2 Environmental precautions

Do not allow material to contaminate ground water system. Prevent product from entering drains.

6.3 Methods and material for containment and cleaning up

Prevent further leakage or spillage if safe to do so. Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13).

6.4 Reference to other sections

Please refer to disposal requirements or country specific disposal requirements for this material. See Section 13 for further information.

7. Handling and Storage

7.1 Precautions for safe handling

INSTRUCTIONS FOR SAFE HANDLING: Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Vapours may form explosive mixtures with air. Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits. Electrical equipment should be protected to the appropriate standard. Preparation may charge electrostatically: always use earthing leads when transferring from one container to another. Use only in area provided with appropriate exhaust ventilation. To avoid ignition of vapours by static electricity discharge, all metal parts of the equipment must be grounded. Wear personal protective equipment. Do not breathe vapours or spray mist. Use only explosion-proof equipment. Keep away from sources of ignition - No smoking.

PROTECTION AND HYGIENE MEASURES: Wash hands before breaks and at the end of workday. When using, do not eat, drink or smoke.

7.2 Conditions for safe storage, including any incompatibilities

CONDITIONS TO AVOID: Direct sources of heat

STORAGE CONDITIONS: Store in original container. Keep locked up or in an area accessible only to qualified or authorised

persons. Store in a dry, well ventilated place away from sources of heat, ignition and direct sunlight

7.3 Specific end use(s)

No specific advice for end use available.

8. Exposure Controls/Personal Protection

8.1 Control parameters

Ingredients with Occupational Exposure Limits (EU)

Name	%	LTEL ppm	STEL ppm	STEL mg/ m3	LTEL mg/ m3	OEL Note
xylene	10-25	50	100	442	221	SK
trizinc bis(orthophosphate)	2.5-10					
ethylbenzene	2.5-10	100	200	884	442	SKIN
titanium dioxide	2.5-10					
magnesium carbonate	1.0-2.5					
ethanol	0.1-1.0					
solvent naphtha (petroleum), medium aliph.	0.1-1.0					
a mixture of: butan-2-one oxime; syn-o,o'-di (butan-2-one oxime)diethoxysilane	0.1-1.0					
cobalt 2-ethylhexanoate	0.1-1.0					
bis(2-ethylhexyl) phthalate	<0.1					
butan-1-ol	<0.1					
ethyl acetate	<0.1					

FURTHER INFORMATION: Refer to the regulatory exposure limits for the workforce enforced in each country.

8.2 Exposure controls

Personal Protection

RESPIRATORY PROTECTION: Respirator with a vapor filter.

EYE PROTECTION: Tightly fitting safety goggles.

HAND PROTECTION: Rubber or plastic gloves. Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact). Long sleeved clothing. Remove and wash contaminated clothing before re-use.

OTHER PROTECTIVE EQUIPMENT: No Information

ENGINEERING CONTROLS: Avoid contact with skin, eyes and clothing. Ensure adequate ventilation, especially in confined areas.

9. Physical and Chemical Properties

9.1 Information on basic physical and chemical properties

Appearance:	Viscous Liquid
Physical State	Liquid
Odor	Solvent
Odor threshold	
pH	
Melting point /freezing point (°C)	Not determined
Boiling point/range (°C)	77 - 385
Flash Point, (°C)	19
Evaporation rate	Slower than ether
Flammability (solid, gas)	Not determined

Upper/lower flammability or explosive limits	1.9 - 19
Vapour Pressure	
Vapour density	Heavier than air
Relative density	1.45 - 1.49
Solubility in / Miscibility with water	Insoluble
Partition coefficient: n-octanol/water	Not determined
Auto-ignition temperature (°C)	Not determined
Decomposition temperature (°C)	Not determined
Viscosity	80 - 95 kU
Explosive properties	Not determined
Oxidising properties	Not determined

9.2 Other information

VOC Content g/l:	445
Calculated grams of VOC per liter of coating product as applied.	
Specific Gravity (g/cm³)	1.472

10. Stability and Reactivity

10.1 Reactivity

No reactivity hazards known under normal storage and use conditions.

10.2 Chemical stability

Stable under recommended storage conditions. Risk of ignition.

10.3 Possibility of hazardous reactions

Hazardous polymerisation does not occur.

10.4 Conditions to avoid

Direct sources of heat

10.5 Incompatible materials

Strong oxidizing agents.

10.6 Hazardous decomposition products

Carbon dioxide (CO₂), carbon monoxide (CO), oxides of nitrogen (NO_x), dense black smoke.

11. Toxicological Information

11.1 Information on toxicological effects

Acute Toxicity:

Oral LD50:

Inhalation LC50:

Irritation: No information available.

Corrosivity: No information available.

Sensitization: No information available.

Repeated dose toxicity: No information available.

Carcinogenicity: No information available.

Mutagenicity: No information available.

Toxicity for reproduction: No information available.

If no information is available above under Acute Toxicity then the acute effects of this product have not been tested. Data on individual components are tabulated below:

<u>CAS-No.</u>	<u>Chemical Name</u>	<u>Oral LD50</u>	<u>Dermal LD50</u>	<u>Vapor LC50</u>
1330-20-7	xylene	4300 mg/kg, rat, oral		15000 ppm/4 hrs rat, inhalation
7779-90-0	trizinc bis(orthophosphate)	552 mg/kg, oral rat		
100-41-4	ethylbenzene	3500 mg/kg rat, oral		
13463-67-7	titanium dioxide	10000 mg/m ³ , oral (rat)		
64-17-5	ethanol	7060 mg/kg, oral, rat		20000 ppm/10 hrs, rat, inhalation
64742-88-7	solvent naphtha (petroleum), medium aliph.	>2000 mg/kg, oral, rat		
117-81-7	bis(2-ethylhexyl) phthalate	30,600 mg/kg, oral, rat		
71-36-3	butan-1-ol	2500 mg/kg rat, oral		800 ppm / 4hrs rat, inhalation
141-78-6	ethyl acetate	5600 mg/kg oral, rat		56000 mg/l/4h. (rat)

Additional Information:

No Information

12. Ecological Information

12.1 Toxicity:

EC50 48hr (Daphnia): No information

IC50 72hr (Algae): No information

LC50 96hr (fish): No information

12.2 Persistence and degradability: No information

12.3 Bioaccumulative potential: No information

12.4 Mobility in soil: No information

12.5 Results of PBT and vPvB assessment

The product does not meet the criteria for PBT/vPvB in accordance with Annex XIII.

12.6 Other adverse effects:

No information

<u>CAS-No.</u>	<u>Chemical Name</u>	<u>EC50 48hr</u>	<u>IC50 72hr</u>	<u>LC50 96hr</u>
1330-20-7	xylene	No information	No information	
7779-90-0	trizinc bis(orthophosphate)	No information	No information	
100-41-4	ethylbenzene	No information	No information	
13463-67-7	titanium dioxide	>100 mg/l (EC50, 48h, Daphnia magna OECD202)ation	No information	>1000 mg/l
546-93-0	magnesium carbonate	No information	No information	
64-17-5	ethanol	No information	No information	
64742-88-7	solvent naphtha (petroleum), medium aliph.	No information	No information	
96-29-7	a mixture of: butan-2-one oxime; syn-o,o'-di (butan-2-one oxime)diethoxysilane	No information	No information	
136-52-7	cobalt 2-ethylhexanoate	No information	No information	
117-81-7	bis(2-ethylhexyl) phthalate	No information	No information	
71-36-3	butan-1-ol	No information	No information	
141-78-6	ethyl acetate	No information	No information	

13. Disposal Considerations

13.1 WASTE TREATMENT METHODS: Do not burn, or use a cutting torch on, the empty drum. If recycling is not practicable, dispose of in compliance with local regulations. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport Information

14.1	UN number	UN 1263
14.2	UN proper shipping name	Paint
	Technical name	
14.3	Transport hazard class(es)	3
	Subsidiary shipping hazard	
14.4	Packing group	II
14.5	Environmental hazards	
14.6	Special precautions for user	Not applicable
	EmS-No.:	
14.7	Transport in bulk according to Annex II of MARPOL 73/78 and the IBC code	Not applicable

15. Regulatory Information

15.1 Safety, health and environmental regulations/legislation for the substance or mixture:

National Regulations:

Denmark Product Registration Number:

Danish MAL Code:

Sweden Product Registration Number:

Norway Product Registration Number:

WGK Class:

15.2 Chemical Safety Assessment

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

16. Other Information**Text for GHS Hazard Statements shown in Section 3 describing each ingredient**

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H351	Suspected of causing cancer.
H360	May damage fertility or the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H413	May cause long lasting harmful effects to aquatic life.

Reasons for revision

No Information

List of References:

This Safety Data Sheet was compiled with data and information from the following sources:

The Ariel Regulatory Database provided by the 3E Corporation in Copenhagen, Denmark
 ESIS (The European Chemical Substances Information System), provided by the European Commission
 Joint Research Centre in Ispra, Italy
 Annex VI of the EU Council Directive 67/548/EEC
 Council Directive 67/548/EEC - Annex I or EU Council Directive 1999/45/EC
 European Union (EC) Regulation No. 1272/2008 on the classification, labelling and packaging of
 substances and mixtures (CLP Regulation)
 EU Council Decision 2000/532/EC and its Annex entitled "List of Wastes"

Acronym & Abbreviation Key:

CLP	Classification, Labeling & Packaging Regulation
EC	European Commission
EU	European Union
US	United States
CAS	Chemical Abstract Service
EINECS	European Inventory of Existing Chemical Substances
REACH	Registration, Evaluation, Authorization of Chemicals Regulation
GHS	Globally Harmonized System of Classification and Labeling of Chemicals
LTEL	Long term exposure limit
STEL	Short term exposure limit
OEL	Occupational exposure limit
ppm	Parts per million
mg/m ³	Milligrams per cubic meter
TLV	Threshold Limit Value
ACGIH	American Conference of Governmental Industrial Hygienists
OSHA	Occupational Safety & Health Administration
PEL	Permissible Exposure Limits
VOC	Volatile organic compounds
g/l	Grams per liter
mg/kg	Milligrams per kilogram
N/A	Not applicable

LD50	Lethal dose at 50%
LC50	Lethal concentration at 50%
EC50	Half maximal effective concentration
IC50	Half maximal inhibitory concentration
PBT	Persistent bioaccumulative toxic chemical
vPvB	Very persistent and very bioaccumulative
EEC	European Economic Community
ADR	International Transport of Dangerous Goods by Road
RID	International Transport of Dangerous Goods by Rail
UN	United Nations
IMDG	International Maritime Dangerous Goods Code
IATA	International Air Transport Association
MARPOL	International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978
IBC	International Bulk Container

For further information, please contact: Technical Services Department

The information on this sheet corresponds to our present knowledge. It is not a specification and it does not guarantee specific properties. The information is intended to provide general guidance as to health and safety based upon our knowledge of the handling, storage, and use of the product. It is not applicable to unusual or non-standard uses of the product or where instructions and recommendations are not followed.

