

## Selection & Specification Data

|                                  |   |
|----------------------------------|---|
| <b>Generic Type</b>              | Single package high alkaline liquid degreaser.  |
| <b>Description</b>               | Carboclean 252 is a highly concentrated heavy alkaline cleaner for use through foam generating equipment, high pressure cleaner, steam cleaner, floor scrubber and immersion tanks. Very effective as a cold soak tank cleaner. Carboclean 252 is designed for use on concrete and ferrous metals only. |
|                                  | <b>NOTE:</b> Ensure correct disposal of spent material.   |
| <b>Colour</b>                    | Light Amber   |
| <b>Theoretical Coverage Rate</b> | 10m <sup>2</sup> /litre of ready to use solution  |
|                                  | <b>NOTE:</b> Material losses during mixing and application will vary and must be taken into consideration when estimating job requirements.   |

## Application Equipment

|              |   |
|--------------|---|
| <b>Spray</b> | Use a foam generator as required.   |
| <b>Brush</b> | Use a medium bristle brush for small areas and soft bristle brooms for large areas.               |
|              | Wash thoroughly with potable water to remove all Carboclean 252 prior to preparation and coating. |

## Mixing & Thinning

|               |  |
|---------------|--|
| <b>Mixing</b> | For cleaning concrete floors using a foam generator or by manual brushing, dilute between 2% and 20%, depending upon the type and degree of soiling, i.e. add 2 litres to 10 litres water. |
|               | For cleaning engines, chassis and under carriages using steam or high pressure washers, dilute Carboclean 252 to between 0.5% and 1.5% with water.   |
|               | For cleaning ferrous metals using a foam generator, dilute to 20% with water (1:4 parts).  |

## Cleanup & Safety

|                |   |
|----------------|---|
| <b>Cleanup</b> | Use water to clean up.  |
| <b>Safety</b>  | Carboclean 252 is highly alkaline and should be treated accordingly. Wear protective clothing when handling. In the event of contact with skin, flush immediately with water and diluted vinegar. Eye contact should be treated immediately by flushing with copious amounts of water prior to seeking medical attention. |
| <b>Caution</b> | Always mix in plastic containers, not metal. Always add Carboclean 252 to water, not vice versa.  |

## Packaging, Handling & Storage

|   |                                       |                          |
|---|---------------------------------------|--------------------------|
| <b>Shipping Weight (Approximate)</b>      | Carboclean 252                        | <b>25 Litre</b><br>29 kg |
| <b>Storage Temperature &amp; Humidity</b> | 4 to 65°C<br>0 to 100%                | Store indoors            |
| <b>Shelf Life</b>                         | 24 Months minimum when stored at 25°C |                          |

**\*Shelf Life: (actual stated shelf life) when kept at recommended storage conditions and in original unopened containers.**



Co. Reg. No.: 1996/01848/07  
Tel No: +27 11 254 5500  
Website: [www.carboline.co.za](http://www.carboline.co.za)  
E-mail: [carboline@carboline.com](mailto:carboline@carboline.com)

February 2017 replaces June 2011

To the best of our knowledge the technical data contained herein is true and accurate on the date of publication and is subject to change without prior notice. User must contact StonCor Africa to verify correctness before specifying or ordering. No guarantee of accuracy is given or implied. We guarantee our products to conform to StonCor Africa quality control. We assume no responsibility for coverage, performance or injuries resulting from use. Liability, if any, is limited to replacement of products. NO OTHER WARRANTY OR GUARANTEE OF ANY KIND IS MADE BY STONCOR AFRICA, EXPRESS OR IMPLIED, STATUTORY, BY OPERATION OF LAW, OR OTHERWISE, INCLUDING MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. Carboline® and Carboguard® are registered trademarks of Carboline Company.