

ALKALI RESISTANT PENETRATION PRIMER

**SOLUTION COATING WITH DEEP PENETRATING PROPERTIES
VAPOUR PERMEABLE FILM ALLOWING BREATHABILITY
EXCELLENT ADHESION TO POROUS SUBSTRATES
RESISTS MILDEW AND FUNGUS GROWTH**

PRODUCT DESCRIPTION:

A high quality wall coating ideal for porous substrates such as new and old plaster, fibreboard and concrete surfaces. Ideal as a primer for subsequent coats of high quality adhesion promoted acrylic paints such as Pro-Struct 684/4 Muralflex and Pro-Struct 684/6.

RESISTANCE:

Excellent resistance to substrate alkali attack, severe weather conditions, mildew and fungus growth and general household detergent washing.

SURFACE PREPARATION:

All surfaces to be sound, clean and dry before application.

On freshly plastered surfaces, allow plaster to dry out and remove dust before application.

APPLICATION:

If substrates are very porous, they should be sealed by diluting Pro-Struct 689 with 10% Carboline Thinner # 10 prior to coating. Apply 2 to 3 coats by brush, roller or airless spray at the following spread rates:

- Flat surfaces using a medium nap roller: 6 to 8m²/litre/coat
- Rough irregular surfaces using a brush or spray: 4 to 6m²/litre/coat

STORAGE:

Store between 4°C to 43°C

TYPICAL PROPERTIES AT 25°C

Type	Solution masonry paint
Volume Solids	36%
Finish	Slight textured matt finish
Colour	White
Drying Time	3 to 4 Hours at 25°C
Overcoat Time	4 Hours at 25°C
Spread Rate	6 to 8m ² /litre on flat surface
Application	Brush, roller, airless spray
Cleaner	Pro-Struct 105 Brush Cleaner
Shelf Life	12 Months
VOC Content	500g/l